

BRIGHTSIGN XD

TRUE 4K DOLBY VISION™ AND HDR10 PLAYBACK. ADVANCED PERFORMANCE.

BrightSign XD delivers superior technology for advanced applications, including 4K video decoding supporting all the technology standards of the True 4K ecosystem: H.265/H.264-encoded native 4K content at 60fps, Dolby Vision, HDR10 and HDMI 2.0a for stunning picture quality. It is also capable of 4K upscaling and dual decoding two 1080p60 videos at once. All models include Gigabit Ethernet and offer a hardware-accelerated HTML5 engine with advanced performance.



BrightSign XD234 Standard I/O Player

Offers video decoding of one 4Kp60 video or two Full HD videos simultaneously and supports Dolby Vision and HDR10 content. It includes the standard I/O package of Gigabit Ethernet, GPIO, IR, analog/digital audio, and an M.2 SSD PCIe interface.

Price: \$450



BrightSign XD1034 Expanded I/O Player

Includes all the features BrightSign XD234 plus additional interactive options with the added serial and dual USB 2.0 (type A and C) ports for engaging interactive displays.

Price: \$550

Features



4K60p single decode



Dolby Vision



HDR10 & HLG



1080p60 dual decode



H.265



Advanced HTML5



IP Streaming



BrightBeacon™



BrightWall™



AutoWall™



Zones



Interactive



Live Feeds



Geo-Fencing



Tagging



BrightSign App



Sign Preview



Remote Snapshot



B-Deploy



Digital Audio



Mosaic Mode



M.2 SSD PCIe Interface

SPECIFICATIONS

| MODEL | XD234 | XD1034 |
|--|------------------------------|--------|
| VIDEO ENGINE DECODER | | |
| Native 4K@60p Dolby Vision and HDR10 video decoding | X | X |
| Single video decoding: 4K or 1080p60 | X | X |
| Dual video decoding: 1080p60 | X | X |
| MEDIA FORMATS | | |
| Video Codecs for 4K content: H.265/H.264 | X | X |
| Video Containers for 4K H.265/H.264 content: .ts, .mov, .mp4, .mkv | X | X |
| Video Codecs for Full HD: H.265, H.264 (MPEG-4 Part 10), MPEG-2 | X | X |
| Video Containers for Full HD content: .ts, .mpg, .vob, .mov, .mp4, .m2ts | X | X |
| Image support BMP, JPEG, PNG | X | X |
| Audio: MP2, MP3, AAC, and WAV (AC3 is passed through) | X | X |
| HTML5 | X (Advanced) | |
| DISPLAY RESOLUTIONS* | | |
| 4K resolutions: 4096x2160, 3840x2160, 3840x600 | X | X |
| Upscaling to: 3840x2160x24/25/29.97/30p | X | X |
| 1920x1080, 1920x1200, 1600x1200, 1440x1050, 1440x900, 1360x768, 1280x1024, 1280x960, 1280x800, 1280x768, 1280x720, 1024x768, 800x600, 720x576, 720x480, 640x480 | X | X |
| HARDWARE INTERFACES | | |
| Locking Power Connector | X | X |
| External micro SD Slot (SDHC and SDXC); SDHC storage up to 32GB SDXC storage up to 2TB | X | X |
| M.2 SSD PCIe Interface | X | X |
| USB High Speed Host Port (also supports content updates) | X (2 ports: Type A&C) | |
| 12-pin Phoenix GPIO port with 8 bi-directional GPIOs | X | X |
| 3.5mm RS-232 Serial Port | X | |
| 3.5mm IR In/Out | X | X |
| 3.5mm Audio Out (analog -or- SPDIF digital, non-simultaneous) | X | X |
| HDMI 2.0a Out | X | X |
| Ethernet | X (Gigabit) | |
| M.2 (E) Keyed Wi-Fi/Bluetooth Connector | X | X |
| Wi-Fi External Antenna Connector | X | X |
| Status LEDs | Power, Busy, Wireless, Error | |
| Reset and Service Buttons | X | X |
| Real Time Clock | X | X |
| FEATURES | | |
| H.265 Decoding: smaller file sizes and higher quality content than H.264 | X | X |
| Native 4K Dolby Vision and HDR10 decoding, 4K upscaling, dual 1080p video decoding | X | X |
| HTML5: hardware-accelerated HTML5 engine plays full screen and modular HTML5 assets up to 4K resolution layered together with high-bandwidth Full HD or 4K video | X (Advanced) | |

| MODEL | XD234 | XD1034 |
|---|---|-------------------------------------|
| BrightBeacon™: 2-way Bluetooth/Beacon communication between mobile devices & signage (requires: wireless/Bluetooth module) | X | X |
| BrightWall™: frame-accurate synchronized playback across multiple displays | X | X |
| Autowall™: embraces the power of HTML5 to create unique multimedia video walls | X | X |
| Zones: playback multiple content types on a single screen | X | X |
| Mosaic Mode: simultaneously play a multitude of smaller resolution videos that add up to the maximum video resolution of the player | X | X |
| IP Streaming: play streaming media | X | X |
| Interactivity: connect virtually any type of interactive device to a multitude of interactive ports | X (GPIO, IR, UDP) | X (GPIO, dual USB, serial, IR, UDP) |
| Live Feeds: Live Data, Live Text, MRSS, Twitter, Flickr, etc. | X | X |
| Tagging: BrightSign Network users can assign media and player tags for highly targeted content distribution | X | X |
| BrightSign App: update signs with an iOS device | X | X |
| Geo-Fencing: trigger playback based on location (requires USB dongle) | X | |
| Sign Preview: preview presentation playback in BrightAuthor | X | X |
| Remote Snapshot: remotely view a snapshot image of the display's playback | X | X |
| Networking: update, manage and schedule your signage | X | X |
| B-deploy: A setup feature to deploy many players at once | X | X |
| Extended Thermal: sustained ambient temperatures between -20°C and 50°C with transients up to 70°C at 90% max relative humidity, non-condensing | X | X |
| SOFTWARE | | |
| Free BrightAuthor Software | X | X |
| BrightSign Networking Options | X | X |
| ACCESSORIES | | |
| USB Button Pads | X | |
| Wireless/Bluetooth Module | X | X |
| MicroSD Class 10 Cards (various capacities) | X | X |
| MISCELLANEOUS | | |
| Dimensions (W x H x D) | 179.9 x 21.9 x 204.2mm or 7.1 x 0.86 x 8 in | |
| Weight | 20 oz | |
| Power | 12V / 3A (36 Watts) | |
| Multi-Country Power & Regulatory Approvals | X | X |
| Built-in Wall Mounting Brackets | X | X |
| 1 year warranty, parts and labor | X | X |



Nowe Technologie IT

ul. Dworcowa 8
43-200 Pszczyna
sklep@unikomp.pl
www.wyswietlanie.pl

Telefony
(32) 210 22 11
(32) 326 33 00
(32) 212 88 22