

Aqualite Outdoor Touch Screen You're in control!

AQUALITE
IP66
WHATEVER THE
WEATHER



Weatherproof IP66 Rated Outdoor 'Intelligent' Touch-Screen!

With all of the qualities & reliability of Europe's leading manufacturer of the Aqualite Outdoor IP66 rated screen, we are proud to announce the **Aqualite Outdoor IP66 Interactive Touch Screen**.

They open up a whole new market, customer and audience!

- ✓ Tested under extreme conditions
- ✓ Used under extreme conditions
- ✓ Sizes : 32", 42", 55", 65" & 82" both in Standard & High Brightness

Relied upon and ideal for....

- ✓ Hotel & Hospitality
- ✓ Pubs, Bars and Nightclubs
- ✓ Education
- ✓ Garden Centres
- ✓ Stadiums
- ✓ Swimming Pools
- ✓ Golf Courses
- ✓ Wildlife Parks
- ✓ Vehicle Advertising & Vending
- ✓ Museums, Zoos and Visitor Attractions
- ✓ Retail / Shopping Malls



OUTSIDE

Let your customers enjoy and interact with your content outside! Educate, interact and have fun!



SELECT

Let your customer browse and select your products AND generate revenue!



WI-FI

With an in-built Wi-Fi enabled PC, it's like a huge tablet!

AVAILABLE NOW! see SKU's overleaf

Call: **+44 (0) 207 449 1775**

Or visit: **www.aqualiteoutdoor.com**



KEY BENEFITS

- Can be used in **Landscape or Portrait**
- Resistive capacitive internal 'Touchfoil' is integrated within our **IP66 toughened glass**, therefore no external overlay is required, improving looks whilst removing any risk if rain, snow or dust is in the air.
- **Touch the surface** of the strong tempered glass a false inaccurate reading will NOT occur. The electrical impulse from your finger does the trick
- **Opens up a whole NEW type of customer** audience i.e. "Outdoor" & create a revenue stream
- **Works outside 24/7** whatever the weather
- **Update information** in "Real-Time" using either the in-built Wi-Fi enabled PC or the hard-wired RJ45
- **2 Touch Sensors** allows the same/**similar use as an tablet** i.e. drag/drop, highlight etc.
- **Effective Communication** with your audience & improve your corporate image
- **Drive sales** with a 24 hour sales lead generation assistant
- Customers will now have access to your complete business portfolio or disseminated content

- **Attract & hold customers attention** at YOUR location- increasing the opportunity for them to buy your product/ service and not your competitors
- Update staff on the key company messages therefore creating a more informed & efficient workforce
- **Fun and engaging to use**

KEY FEATURES

- Standard Brightness (500cd/m2) & High Brightness (1500cd/m2) models
- Multi-point touch screen capability - Fun and easy to use!
- In-built Windows PC - Refresh your content remotely via the internet
- In-built Digital TV Tuner (European Standard)
- Wide viewing angle (170°)
- Working temperature (-20°C - +55°C)
- Working humidity (10% - 90%)
- Toughened tempered glass



Model/SKU	AQPCH-32-TOUCH	AQPCH-42-TOUCH	AQPCH-55-TOUCH	AQPCH-65-TOUCH	AQPCH-82-TOUCH
High Brightness	1500 Nits (cd/m2)	1500 Nits (cd/m2)	1500 Nits (cd/m2)	1500 Nits (cd/m2)	1500 Nits (cd/m2)
Model/SKU	AQPCS-32-TOUCH	AQPCS-42-TOUCH	AQPCS-55-TOUCH	AQPCS-65-TOUCH	AQPCS-82-TOUCH
Standard Brightness	500 Nits (cd/m2)	500 Nits (cd/m2)	500 Nits (cd/m2)	500 Nits (cd/m2)	500 Nits (cd/m2)
LCD Panel	32inch	42inch	55inch	65inch	82inch
Resolution	1920x1080p	1920x1080p	1920x1080p	1920x1080p	1920x1080p
Integral TouchFoil™	2 Touch (multi-point)	2 Touch (multi-point)	2 Touch (multi-point)	2 Touch (multi-point)	2 Touch (multi-point)
Accuracy	>1.5% of diagonal				
Response time	10-20ms				
Touch Function	Native Windows Touch function for Windows7, 8, 8.1				
Software Compatibility	Windows7, 8, 8.2 (mouse and touch)				
Touch Detection	18mic Ø wire				
Damage Immunity	No moving parts				
Contrast Ratio	10,000:1	10,000:1	10,000:1	10,000:1	10,000:1
Response time	6 ms	6 ms	6 ms	6 ms	6 ms
Viewing angle	170*	170*	170*	170*	170*
Glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass	Tempered AR glass
IP Certificated	IP66	IP66	IP66	IP66	IP66
Power supply	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug	100-240V 50-60Hz UK 3-pin plug
Working temp	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)	(- 20°C to + 55°C)
Working humidity	10% - 90%	10% - 90%	10% - 90%	10% - 90%	10% - 90%
Speakers	Yes	Yes	Yes	Yes	Yes
Media support	USB interface	USB interface	USB interface	USB interface	USB interface
Play format	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more	MPEG 1-4 & more
Tuner format	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV	ATV & DTV
Control	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**	IR & RS232**
Boxed weight (AQPCH)	45 kg	52 kg	89 kg	128 kg	300 kg
Net weight (AQPCH)	35 kg	43 kg	71 kg	106 kg	201 kg
Boxed weight (AQPCS)	40 kg	49 kg	86 kg	106 kg	300 kg
Net weight (AQPCS)	30 kg	39 kg	76 kg	97 kg	201 kg
Box dimensions (mm)	L990xH710xD233	L1225xH855xD233	L1560xH1015xD233	L1780xH1150xD233	L2500xH1500x350
Screen dimensions (mm)	L866xH581xD93	L1087xH685xD93	L1419xH844xD138	L1641xH976xD138	L2011xH1182xD145
Inputs	HDMI, VGA, Componet, RF (aerial), S-Video, Composite (RCA), Audio left/right (RCA), RS2323, USB				
Outputs	RS232* (Please note that all current RS232 functionality should be checked with manufacturer before purchase)				

Internal PC Specifications. We can BESPOKE BUILD to any PC Specification!

i3 Celeron 1037U Dual Core 1.8GHz CPU
 4 GB Ram
 120-GB Micro SSD Drive Kingston (UPGRADABLE to any SPECIFICATION)
 Output Ports:-2 x HDMI, 2 x USB, 1 x USB3, 1xSerial Port, Audio WG825741 Gigabit Ethernet,
 2 x Optional Wi-Fi Antenna.
 36W AC Adapter (internal)
 Windows (7 or 8) Professional 64bit or 32-bit as required.

* Specifications correct at time of going to press

For more information call:
+44 (0) 207 449 1775

Or visit our website:

www.aqualiteoutdoor.com

12 England's Lane, Hampstead, London, NW3 4TG