

AVer VB342

Video Soundbar

Ultra HD 4K Camera Soundbar for Huddle Room



Package Contents

- VB342 unit
- Remote control
- 1.8m USB cable to PC (USB 3.0 type C to PC)
- USB type-A to type-C adapter
- Power supply
- Quick-start guide
- Wall mount bracket
- Mounting screws

Camera

- Sensor: 1/2.5" Sony Exmor R™ 4K CMOS sensor
- Frame rate: 4K 30fps; 1080p, 720p, 960x540, 848x480, 640x480, 640x360, 424x240, 320x240, 320x180 at 60, 30, 15 fps
- Lens iris, focus, zoom: fixed
- AE, white balance: auto, manual override by PTZApp
- Field of view: diagonal 94°, horizontal 85°, vertical 55°
- Back light compensation
- Minimum working distance: 80cm
- Motor pan and tilt, total horizontal viewing area 165°; vertical viewing area 85°
- Digital zoom rate: up to 4X leveraging 4K sensor

Audio

- Microphones, 2 uni-directional microphones supporting pick up 6m range
- 5W stereo full range speakers with professional bass port tuned for communication
- Volume up to 96dB SPL at 1/2 meter
- Echo cancellation
- Noise suppression
- 3.5mm Line-in (aux) cable connects to BYOD smartphones or PC as speakerphone

HDMI

- DisplayLink USB 3.0 to HDMI adapter built-in
- 1080p HDMI output to TV**

** Some limitation applied by Mac OSX and Windows inbox driver

** DisplayLink doesn't support Chrombox

Remote Control

- 10 camera presets (3 presets via remote control)

System Requirements*

- Windows 7/8/8.1/10
- Mac OS X 10.7 or higher
- Android 7.0 or later

Hardware Requirements*

- 2.4GHz Intel Core 2 Duo processor
- 2GB RAM or more

Power Supply

- AC 100V ~ 240V
- Consumption: DC12V/5A

Free Applications for Meeting Collaboration (Free Apps support on Windows® and Mac® computers)

PTZApp

- Compatible with Skype™ Plugin for answering and hanging up via remote control
- Upgrade firmware automatically or manually
- Control camera
- Set parameters and adjust camera image
- Diagnose operating status
- View live video

EZLive

- Real-time streaming / annotating / snapshots / video recording

Environmental Data

- Physical characteristics: 0~40°C
- Operation humidity: 20%~80%
- Storage temperature: -20~60°C
- Storage humidity: 20%~80%

Physical Characteristics

- Package dimensions: 739 x 193 x 229mm
- Package weight: 4.16kg/9.3lbs
- CameraSoundbar: 650 x 100 x 109.5mm/2.133kg
- Remote control: 150 x 45 x 10mm/0.040kg

Video format

YUV and MJPEG

Warranty

- Camera, speakerphone: 3 years (online registration for 2 years extended warranty)
- Accessories: 1 year

Compatible Applications

Adobe Connect, BlueJeans, CyberLink U Meeting®, Cisco WebEx®, fuze, Google Hangout, GoToMeeting™, Intel® Unite™, LiveOn, Microsoft® Lync™, Skype™, Skype for Business, TrueConf, V-Cube, Vidyo, vMix, WebRTC, Wirecast, XSplit, ZOOM

Optional Accessories


- 5M USB 2.0 type-A to type-C cable
- 10M Expansion Microphone

* For Full HD support, please check with your software application provider for system/hardware requirements.

Hardware Specifications



Back panel



UniKomp.pl
Nowe Technologie IT

adres	43-200 Pszczyna, ul. Piastowska 9
tel/fax	(32) 2102211, 3263300, 2128822
e-mail	sklep@unikomp.pl
internet	www.wyswietlanie.pl