

Ultra Stretch Signage | 88BH7F

Ultra Stretch Signage, 32:9 Space-Fitting Wide Screen

The 88BH7F is the most suitable display for delivering new forms of advertising and multiplexed information in a 32:9 widescreen format that brings you a new experience, captivating customers' attention.



32:9 Wide Screen



High Picture Quality



Effective Content Delivery



Efficient Operation



UniKomp.pl

Nowe Technologie IT

ul. Dworcowa 8
43-200 Pszczyna
sklep@unikomp.pl
www.wyswietlanie.pl


Telefony
(32) 210 22 11
(32) 326 33 00
(32) 212 88 22



* All images are for illustrative purposes only.


32:9 Extended Wide Format

It is a unique wide screen with 32:9 bar type which provides much more flexibility in playing content than the conventional display of 16:9 ratio.



Ultra HD Resolution (3,840 x 1,080)

Ultra HD resolution delivers an immersive viewing experience with vivid colors and clear images.



Flexibility for Content Management

The 88BH7F is able to organize multi content with video and text according to user's desired ratio. Also, it is optimized to show a vertical or horizontal object without truncation, providing lifelike viewing experiences to the customers.



Multi Screen Mode with 4PBP

The Picture-by-Picture (PBP) feature allows you to show multi content in one single display by up-to four parts. It is very useful and convenient to deliver various advertisements or pieces of information at the same time without calibration.



High Performance SoC with webOS

Built-in Quad Core SoC can execute several tasks at once while providing smooth content playback without the need for a media player. Also LG webOS platform enhances user convenience with intuitive GUI and simple app development tools.



Tiled Scene with DP Daisy Chain


The 88BH7F can show a tiled scene through its DP Daisy Chain*. This will be the best choice if you want to use a large screen, or provide visual impact to your customers in a different way.



* DP Daisy Chain supports up to 4x4 configuration.

LAN Daisy Chain Management

By using this daisy-chained network feature, you can execute commands such as controlling, monitoring and even updating firmware.




Real-Time Monitoring with Signage365Care

Easier and faster maintenance are available with our optional cloud service solution Signage365Care*. It remotely manages the status of displays in client workplaces for fault diagnosis and remote-control services, ensuring the stable operation of clients' businesses.




* The availability of the "Signage365Care" service differs by region, so please contact the LG sales representative in your region for more details.

Dimension (unit: mm)



Connectivity



- 1 AUDIO In
- 2 AUDIO Out
- 3 HDMI(1) In 2.0
- 4 HDMI(2) In 2.0
- 5 DP In
- 6 DP Out
- 7 HDMI(3) In 1.4
- 8 DVI-D In
- 9 USB 2.0 In
- 10 IR & LIGHT SENSOR
- 11 RS-232C In
- 12 RS-232C Out
- 13 LAN In
- 14 LAN Out



* Dimensions & Jack Panels (Read/Side) may differ from the above image, so please contact LG salesteam to verify before ordering.

Specifications

88BH7F

| | | |
|--------------------------------|---|--|
| Panel | Screen Size | 88" |
| | Panel Technology | IPS |
| | Aspect Ratio | 32:9 |
| | Native Resolution | 3,840 x 1,080 (UHD) |
| | Brightness | 700 cd/m2 (Typ) |
| | Contrast Ratio | 1,100:1 (Typ) |
| | Dynamic CR | 500,000:1 (Typ) |
| | Viewing Angle (H x V) | 178 x 178 |
| | Response Time | 8ms (G to G BW, Typ) |
| | Surface Treatment | AGLR (Haze 3%) |
| Lifetime | 50,000 Hrs (Typ.) | |
| Operation Hours | 24Hrs / 7Days | |
| Orientation | Landscape & Portrait | |
| Connectivity | Input | HDMI (3), DP, DVI-D, Audio, USB 2.0 (2) |
| | Output | DP, Audio |
| | External Control | RS232C In/Out, RJ45 In/Out, IR In |
| Physical Specification | Bezel Color | Black |
| | Bezel Width | 4.4 mm (L/R), 5.9 mm (T/B) |
| | Monitor Dimension (W x H x D) | 2,158.3 x 611.2 x 84.8 mm |
| | Weight (Head) | 33.9 kg |
| | Carton Dimensions (W x H x D) | 2,274 x 717 x 212 mm |
| | Packed Weight | 51.7 kg (Pallet included) |
| Handle | Yes | |
| VESA™ Standard Mount Interface | 600 x 400 mm | |
| Special Features | Internal Memory 8GB(System 4GB, Available 4GB), Built-in Wi-Fi, Temperature Sensor, Auto Brightness Sensor, USB Auto Playback, Local Contents Scheduling, Group Manager, Failover, Image Customization (Booting Logo, No Signal), Content Sync (RS-232C/Local Network), PBP(4), Play via URL, OSD/Content Rotation, Tile Mode Setting (Max. 15x15), Setting Data Cloning (RS-232C/Network/USB), Crestron Connected [®] 1), Control Manager, Smart Energy Saving, DPM, PM Mode, Wake on LAN, HDMI-CEC ²⁾ , webRTC, SI Server Setting | |
| Environment Conditions | Operation Temperature Range | 0 °C to 40 °C |
| | Operation Humidity Range | 10 % to 80 % |
| Power | Power Supply | 100-240V~, 50/60Hz |
| | Power Type | Built-In Power |
| | Power Consumption | Typ. / Max. 450 W / 530 W Smart Energy Saving 210 W |
| Standard (Certification) | Safety | IEC 60950-1 / EN 60950-1 / UL 60950-1 |
| | EMC | FCC Class "A" / CE / KC |
| | ErP / Energy Star | Yes / N/A |
| Media Players Compatibility | OPS Type Compatible | Yes |
| | External Media Player Attatchable | No |
| Software Compatibility | Content Management Software | SuperSign CMS |
| | Control and Monitoring Software | SuperSign Control/ Control+ |
| | Signage365Care | Yes |
| Accessories | Basic | Remote Controller, Power Cord, DP (2.6M), RS-232C Cable (3M) |
| | Optional | KT-OPSA(OPS Kit) |

1) Network based control 2) Compatibility may differ by equipment



- www.lg.com/b2b
- www.youtube.com/c/LGECCommercialDisplay
- www.facebook.com/LGInformationDisplay
- www.linkedin.com/company/LGInformationDisplay

LG may make changes to specifications and product descriptions without notice.
Copyright © 2019 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp.
The names of products and brands mentioned here may be the trademarks of their respective owners.