UniKomp.pl
Nowe Technologie IT
ul. Dworcowa 8
43-200 Pszczyna
sklep@unikomp.pl
www.wyswietlanie.pl
Telefony
(32) 210 22 11
(32) 326 33 00
(32) 212 88 22

vivitek NovoConnect

NovoTouch

LK9820i Collaborative Flat Panel Display





Display	Type/Technology		Backlit D-LED (IPS Panel)
	Panel Size		98"
	Brightness (Typ)		400cd/m2
	Contrast Ratio (Typ)		1,300:1
	Native Resolution		4K Ultra-HD (3840 x 2160)
	Viewing Angle (H/V)		178°/178°
	Aspect Ratio		16:9
	Refresh Rate (Hz)		120Hz
Interactivity	Technology		Infrared Touch
	Touch Points	Writing	10 Point
		Touch	10 Point
	Surface Protection		4mm Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)
	Touch Tools		Finger, Stylus, Glove, Opaque Objects
Operating System	System Version		Android™ v5.0
	CPU		Quad Core ARM Cortex A53 CPU - Up to 1.4GHz
	GPU		Mali™- 450
	RAM		2GB DDR3
	Internal Storage		16GB
Connectivity	Input	Display	HDMI v2 (x4), HDMI v1.4 (x1), VGA-In (x1), YPbPr-In (x1), AV-In (x1)
		Audio	Audio-In (3.5mm) (x1), MIC-In (3.5mm) (x1)
	Output	Display	HDMI-Out v2 (4K@60Hz) (x1), AV-Out (x1)
		Audio	Audio-Out (3.5mm) (x1), SPDIF-Out (x1)
	Internet		RJ45 (x1)
	Control		RS232 (x1)
	USB	Front	USB 2.0 (x2), USB Type B (x1) (For Touch Port)
		Side	USB 2.0 (x2), USB 3.0 (x2), USB Type B (x1) (For Touch Port)
Audio	Speakers		15W (x2) (Stereo)
Power	Power Supply (Internal)		AC 100-240V, 50/60Hz
	Consumption		480W
	Standby Mode		<0.5W (Standby)
Physical Characteristics	Dimension (L x H x D)		2,242 x 1,338 x 117 mm
	Weight		129.43 kg
	VESA Mounting (FPMPMI)		4 - M8, 800 x 600 mm
	Color		Black

©2019 Vivitek.
Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate.
Specifications are subjection to change without prior notice.