

MXRV-7100

16GB, future-proof display controller for GPU-intensive PACS



- **NVIDIA accelerated computing platform**
- **16GB DDR6 display memory with ECC error correction**
- **224 GB/s memory bandwidth**
- **4x Mini-DisplayPort 1.4 (mDP to DP locking adapters included)**
- **Maximum power consumption: 50W**
- **5-year all-inclusive warranty and service support**

High-capacity graphics, ultra-efficient design


With its small size of 69mm x 168 mm, the Barco MXRV-7100 combines powerful graphics performance with an ultra-efficient, low-profile form factor. Equipped with 16GB of DDR6 ECC memory and PCIe Gen4 x8 interface, it offers exceptional bandwidth and responsiveness for demanding imaging applications.

Powered by an NVIDIA accelerated computing platform, the MXRV-7100 graphics card offers an easy way to step into the AI ecosystem and run edge applications on your Barco diagnostic display.

With native DisplayPort connectivity, OpenGL 4.6 support, and no need for an external power connector, this medical-grade graphics card is optimized for modern Windows 10/11 environments. The MXRV-7100 is covered by Barco's 5-year all-inclusive warranty, delivering premium performance with access to Barco's Intuitive Workflow Tools and including dependable support by the Barco team.

Product specifications**MXRV-7100****General specifications**

| | |
|---------------------------|---|
| Bus compatibility | PCI Express Gen4 x8 |
| Power consumption | 50 Watt |
| Form factor | 2.7 inches x 6.6 inches, single-slot |
| Operating system | Windows 10/11 & Server 2019/2022 |
| Platforms | Intel® and AMD architectures |
| Power Connector | No external power connectors |
| Graphics accelerator | NVIDIA® Ada Lovelace® GA107 |
| Display memory | GDDR6 16GB |
| Memory bandwidth | 224 GB/s |
| Pixel depth | 32-bit pixels (supports 8-bit and 10-bit per color channel) |
| Electrical standard | DisplayPort complying to v1.4 |
| Direct3D hardware support | DirectX 12.07, Shader Model 5.17, Vulkan 1.2 |
| OpenGL hardware support | OpenGL 4.6 |
| Connectors | 4x Mini DisplayPort |
| Connectivity | Native DisplayPort suggested, DisplayPort to Single-link DVI adapter available separately |
| Operational temperature | 0° to 45°C |

| | |
|--|---|
|  unikomp. Nowe Technologie IT | ul. Dworcowa 8, 43-200 Pszczyzna +48 (32) 210 22 11, +48 609 610 393 sklep@unikomp.pl www.wyswietlanie.pl |
|--|---|

Last updated: 28 Aug 2025

© 2025 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.