



11.6" Frameless Screen

Resolution: **1920x1080**

Aspect Ratio: **16:9**

Brightness: **450 Nits**

Contrast: **800 CR**

Viewing Angle: **89/89/89/89**

Overall Area: **13.1" x 7.8" x 1.5"**

Mounting: **VESA 100x100mm, M4x6mm**

Model Numbers

Non-Touch: **20-3008-1047**

Touch: **20-3008-1004**

Non-Touch PoE: **20-3008-1048**

Touch PoE: **20-3008-1049**

Bluefin combines ad player and LCD digital signage solutions with industrial grade LCD manufacturing to provide all-in-one solutions for retail advertising, menu boards, interactive experiences and more.

BrightSign[®] Built-In

BrightSign Built-In displays provide a simple, compact solution for digital signage designed to save time and effort. Simplify your installation with a robust, reliable content management ecosystem combined with an industrial quality LCD screen built to fit your project needs.



Feature Snapshot

- H.265 Video Decoding
- Multi-Zone Video Walls
- Standalone or networked interactive screens
- Remote content updates
- HTML5 rendering
- Event logs



Ask about optional touch screens, power over ethernet, and Wi-Fi

Remote Updates

Options to update your content remotely from a PC on your players network, a periodic server location update or BrightSign's powerful cloud based networking solution.



BrightSign Built-In Player Specifications

Audio

- Stereo 3W HDMI Speakers
 - Finished - Internal
 - Framless- External, Optional
- 3.5mm Audio Out (Analog and Digital)

Storage

- Micro SD Slot
 - SDHC up to 32GB
 - SDXC up to 2TB

Network

- RJ45 Ethernet

Input / Output

- 1x USB 2.0
- Phoenix GPIO (4-pin bi-directional terminal block)
- 3.5mm RS-232 Serial Port
- J10: DC 12v 6 pin Power Out
- 3.5mm BrightSign Remote Control Input

Media Formats

- Video Codecs
 - H.265, H.264 (MPEG-4, Part 10), MPEG-2, MPEG-1
- Video Containers
 - .ts, .mpg, .vob, .mov, .mp4, .m2ts, .wmv
- Images
 - BMP, JPEG, PNG
- Audio
 - MP2, MP3, AAC, WAV
- HTML5 (Moderate Usage)

BrightSign Features

BrightBeacon™: 2-way Bluetooth/Beacon communication between mobile devices & signage

BrightWall™ : synchronized playback across multiple displays

Zones: playback multiple content types on a single screen

Mosaic Mode: simultaneously play a multitude of smaller resolution videos that add up to the maximum video resolution of the player

Tagging: BrightSign Network users can assign media and player tags for highly targeted content distribution

BrightSign App: update signs with an iOS device

Geo-Fencing: trigger playback based on location (requires USB dongle)

Remote Snapshot: remotely view a snapshot image of the display's playback

BrightPlates™: easy template-based sign creation service

B-deploy: A setup feature to deploy many players at once



ul. Dworcowa 8
43-200 Pszczyna
sklep@unikomp.pl
www.wyswietlanie.pl

Telefony
(32) 210 22 11
(32) 326 33 00
(32) 212 88 22