


## PS502X - 4,000 LUMEN BUSINESS AND EDUCATION PROJECTOR

### Key Features


- High brightness 4000 Lumens XGA projector with advanced visual features ideal for use in education and small business environments
- Flexible to fit any classroom design with 0.62 short throw ratio. Project 100 inches from a distance of 4 feet (1.24 meters)
- Simple setup and control, just plug & play your presentations, videos, and pictures
- Energy-saving Eco mode allows the lamp to shine bright for up to 12,000 hours
- Supports most media players, PCs, Macs, and mobile devices with input options such as HDMI, USB, VGA, and more



60 - 300 in. / 1.5 - 7.6 m  
**DISPLAY**



**PANEL**



VGA(640 x 480) to FullHD(1920 x 1080)  
**RESOLUTION**



**XGA (1024 X 768p) RESOLUTION**

### Product Description

Light up classrooms and conference rooms alike with the ViewSonic® PS502X XGA short throw projector.

Featuring 4,000 ANSI lumens of stunning brightness, this powerful business and education projector creates crystal clear images up to 300". And with a 0.616 short throw ratio, this projector is capable of displaying shadow-free 100" images from just 4.3 feet away.

The PS502X projector also comes with multiple connectivity options for greater convenience. Dual HDMI ports empower users to connect multiple devices directly to the projector. Once connected, users can conveniently switch between different input sources at the press of a button. A USB-A port provides power to wireless HDMI dongles for a more convenient streaming experience. Rather than taking your projector to the service center, software updates can be performed easily over a simple USB cable.

With the PS502X projector, you can let your presentations shine with stunning clarity.

# Specifications

	More Information
<b>UPC</b>	766907020021
<b>Light Source</b>	DLP Lamp
<b>Display Resolution</b>	XGA (1024x768)
<b>Display Resolution</b>	1024 x 768
<b>Brightness (Lumens)</b>	4,000 ANSI
<b>Screen Size</b>	60 - 300 in. / 1.5 - 7.6 m
<b>Throw Distance</b>	0.75m-3.76m (77" @0.96m)
<b>Throw Ratio</b>	0.61
<b>Keystone</b>	Vertical (+/- 19°)
<b>Lens</b>	Fixed Zoom
<b>Light Source (watt)</b>	240
<b>Light Source Life, Normal (hours)</b>	4000
<b>Light Source Life, Dynamic Eco-Mode (hours)</b>	12000
<b>Color Depth</b>	1.07B Color (R/G/B 10bit)
<b>Dynamic Contrast Ratio</b>	15,000:1
<b>Aspect Ratio</b>	4:3
<b>Input Lag</b>	37ms
<b>Frequency Horizontal</b>	15K-102KHz
<b>Frequency Vertical</b>	23-120Hz
<b>PC Resolution (max)</b>	VGA(640 x 480) to FullHD(1920 x 1080)
<b>Mac® Resolution (max)</b>	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
<b>USB 2.0 Type A</b>	1
<b>3.5mm Audio Out</b>	1
<b>3.5mm Audio In</b>	1
<b>Control (RS232)</b>	1
<b>HDMI 1.4 (with HDCP 1.4)</b>	2
<b>VGA In</b>	1
<b>VGA Out</b>	1
<b>Internal Speakers</b>	16W (x1)
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Consumption (typical)</b>	295W
<b>Stand-by</b>	<0.5W
<b>Physical Controls</b>	Keypad, Power key

**On Screen Display**

Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

**Temperature**

32-104° F (0 - 40° C)

**Kensington Lock Slot**

1

**Net (lbs)**

6.3

**Gross (lbs)**

9

**Net (kg)**

2.87

**Gross (kg)**

4.08

**Packaging (in.)**

15.7 x 13.3 x 6.6

**Physical (in.)**

12.2 x 9.2 x 4.5

**Packaging (mm)**

400 x 337 x 168

**Physical (mm)**

309 x 234 x 115

**Regulations**

cTUVus

**Package Contents**

Projector, power cable, remote control, Quick Start Guide

**Warranty**

3-year limited warranty on parts and labor, 1st year free Express Exchange® service\*\*

**Recycle/Disposal**

Please dispose of in accordance with local, state or federal laws.

UPC: 766907020021



**UniKomp.pl**  
Nowe Technologie IT

ul. Dworcowa 8  
43-200 Pszczyna  
sklep@unikomp.pl  
www.wyswietlanie.pl

Telefony  
(32) 210 22 11  
(32) 326 33 00  
(32) 212 88 22