vivitek
Vivid Color, Vivid Life

DH3331

MULTIMEDIA PROJECTORS



1080p Versatile Installation Projector



FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 5,000 ANSI lumens of brightness, 1080p resolution, and 10,000:1 contrast ratio for clear, crisp and bright projection
- Great flexibility with 1.7x zoom centered lens and manual horizontal and vertical lens shift
- HDBaseT interface for HD video over standard CAT5e/6 LAN cable
- Vertical & horizontal keystone corrections, warp and individual corner adjustments
- 2x 7W speakers and microphone input ensure you are clearly heard
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Built-in 12V trigger for screen and/or blinds control







A brand of DELTA

Feature rich with extensive input options and flexible installation range

The DH3331 offers great features and performance combined with great installation flexibility. The wide screen WUXGA native image resolution and the 5000 ANSI lumens, ensure a bright and sufficient detailed content and a wide range of applications. The 1.25 - 2.13:1 throw ratio (1.7x zoom) en also enables to install the projector in a wide range of distance/screen scenario's. DH3331 features also 3D, JPG reader, optional wireless adapter and HDBaseT.



DH3331 SPECIFICATIONS

Image	**Display Type**	Single chip DLP® Technology by Texas Instruments
	Brightness	5000 ANSI Lumens
	Native Resolution	1080p (1920 x 1080)
	Max. Supported Resolution	WUXGA (1920x1200) @60Hz
	Native Aspect Ratio	16:9
	Contrast Ratio	10000:1
	Keystone Correction	Vertical: +/-30° ; Horizontal: +/-25°
Optical	**Throw Ratio**	1.25 - 2.13:1
	Zoom Ratio	1.7x
	Lens Shift (Based on Full Image Height)	Vertical +28.7%, -13.5%; Horizontal +/-10.3%
	Image Size (Diagonal)	21" - 361"
	Projection Distance	1 - 10m
	Projection Lens	F = 2.45 - 3.22, f = 18.8 - 32 mm
	Offset (Based on Full Image Height)	Manual Lens Shift
Features	**Features**	3D Features, 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock, Wall Color Correction
Compatibility	**Video**	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	**I/O Connection Ports**	VGA-In (15pin D-Sub) (x2), HDMI v1.4 (x2 (HDMI/MHL x1, HDMI x1)), DVI-D, Component (5 BNC) (RGBHV) , Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack) (3), VGA-Out (15pin D-Sub), Audio-Out (RCA), Audio-Out (Mini-Jack), RJ45 (x1 (RJ45/HDBaseT)), IP Telnet Capable Over RJ-45 (False), 12v Trigger (3.5mm mini-jack), RS-232 (True), 3D-Sync Out, USB A (Power Only), USB B (Service), Microphone (Mini-Jack), Remote Jack(wire remote)
General	**Dimensions (W x D x H)**	445 x 331 x 162 mm
	Weight	8.4 kg
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 380W (Eco. Mode), 480W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	1,500/3,500 Hours (Normal/Eco. Mode), 370W/280W
	Speakers	7W x2
	Noise Level	36dB / 33dB (Normal/Eco Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811119760-SVV), 3D Glasses P/N (3534257700), Remote Control P/N (5041846600), 3D Features
	Warranty	Standard Warranty: 3 years projector / 1 year on lamp or 1000 hours whichever comes first
	UPC Code	813097020345

© Copyright 2015 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.
DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands. Tel: + tel: +31 20 655 0960 | fax: +31 20 655 0999 | email: info@vivitek.eu