ViewSonic

PROJECTOR

PA502SP

Key **Features**

Bright Images in Any Environment | SuperColor™: Amazing Colour Performance | Personalized Viewing | Integrated Power Source | Incredible Sounds



Product **Description**

The ViewSonic PA502SP SVGA projector for presentations offers impressive multimedia performance from various devices in small to medium-sized meeting rooms and classrooms. Packed with 3,500 ANSI Lumens of high brightness and SuperColor™ Technology, the projector is guaranteed to project consistent and true-to-life image even in brightly lit environments. It integrates VGA, Composite, HDMI inputs and 2W speaker, fulfilling the needs to project multimedia contents including multimedia devices and online videos. In addition, with the USB Type-A with power supply, it is capable for wireless projection through HDMI wireless dongle for media streaming or mirroring contents from mobile device. This projector also comes with an energy-efficient smart energy feature which reduces power consumption and extends the lamp life to 15,000 hours on average.

Visit Us www.viewsonic.com

UNIKOMP.pl
Nowe Technologie IT
adres 43-200 Pszczyna , ul. Piastowska 9
tel/fax (32) 210 22 11, 3263300, 2128822
e-mail biuro@unikomp.pl
internet www.unikomp.pl

SPECIFICATION

Projection System:	0.55" SVGA
Native Resolution:	800x600
DC Type:	DC3
Brightness:	3500
Contrast Ratio with SuperEco Mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light Source Life:	5000/15000
Lamp Watt:	190W
Lens:	F=2.5-2.7, f=22.08-24.28mm
Projection Offset:	125%+/-5%
Throw Ratio:	1.97-2.17
Image Size:	30" - 300"
Throw Distance:	1.16m-13.42m (100" @ 3.97m)
Keystone:	+/- 40° (Vertical)
Optical Zoom:	1.1x
Audible Noise (Normal/Eco):	30dB
Response Time:	16ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

INPUT

Computer in (share with component):	1
Composite:	1
Audio-in (3.5mm):	1
HDMI (HDCP):	1 (HDMI 1.4/ HDCP 1.4)

OUTPUT

Audio out (3.5mm):	1
Speaker:	2W
USB Type A (Power):	1 (5V/ 1A)

CONTROL

RS232:	1
USB Type Mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 240WStandby: <0.5W
Operating Temperature:	0~40℃
Carton:	Brown
Net Weight:	2.1kg
Dimensions (WxDxH) with Adjustment Foot:	320x210x123mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	1

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-111
Carry Bag:	PJ-CASE-008

UNIKOMP.pl
Nowe Technologie IT
adres 43-200 Pszczyna , ul. Piastowska 9
tel/fax (32) 210 22 11, 3263300, 2128822
e-mail biuro@unikomp.pl
internet www.unikomp.pl

Copyright © ViewSonic Corporation 2000-2018. All rights reserved. (12/19/2018 08:14:28 America/Chicago)