ViewSonic | PROJECTORS
PA502X

Key **Features**

SuperColor™: Amazing Color Accuracy | 3,500 Lumen Brightness | Energy Efficient SuperEco™



Product **Description**

The ViewSonic® PA502X price-performance projector features 3,500 lumens, native XGA 1024 x 768 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. The PA502X also features extensive connectivity including HDMI, VGA, and Composite Video. An energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 15,000 hours. With advanced audio-visual features, flexible connectivity options, and an affordable price, the PA502X is ideal for use in education and small business environments.



1. IR remote sensor
2. Projection lens
3. Elevation foot
4. Focus / zoom rings
5. HDMI
6. Video In
7. RS232
8. AC In
9. Control Panel
10. USB type Mini B
11. VGA
12. Kensington® Lock Slot

1024 x 768
RESOLUTION

3,500
LUMENS

1.97 ~ 2.17
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP
Resolution Type:	XGA
Resolution:	1024 x 768
Brightness (ANSI Lumens):	3,500
Throw Distance:	3.93 - 43.4 ft / 1.20 - 13.23 m
Throw Ratio:	1.97 ~ 2.17
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Keystone:	Vertical (± 40º)
Lens:	1.1x optical zoom
Light Source (watt):	190
Light Source Life, Normal (hours):	5000
Light Source Life, Dynamic Eco-Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	22,000:1
Aspect Ratio:	4:3

Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

Compatibility:

PC Resolution (max):	VGA (640 x 480) to WUXGA_RB (1920 x 1200)
Mac® Resolution (max):	VGA (640 x 480) to WUXGA_RB (1920 x 1200)

Connector:

Mini USB Type B(1), Control (RS232)(1), HDMI 1.4(1), VGA In(1), Composite RCA Video In(1), RGB Input(1)

Power:

Voltage:	AC 100-240V (universal), 50-60Hz
Consumption (typical):	240W
Stand-by:	<0.5W

Operating Conditions:

Temperature:	32-104º F (0 - 40º C)

Weight (imperial):

Net (lbs):	4.63
Gross (lbs):	7.5

Weight (metric):

Net (kg):	2.1
Gross (kg):	3.2

Dimensions (imperial) (WxHxD):

Packaging (in.):	15.04 x 12.44 x 6.54
Physical (in.):	12.60 x 8.26 x 4.83

Dimensions (metric) (WxHxD):

Packaging (mm):	382 x 316 x 166
Physical (mm):	320 x 209.8 x 122.7

General:

Regulations: cTUVus, UL/cUL, FCC (including ICES-003)

PACKAGE CONTENTS: PA502X projector, power cable, VGA cable, remote control, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: 3-year limited warranty on parts and labor, 1st year free Express Exchange® service**

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907914412

Accessories:

PGD-350, PJ-CASE-008, PJ-WMK-006, PM-FCP, RLC-111

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (12/27/2017 02:20 AM PST)

UNIKOMP.pl
Nowe Technologie IT
adres 43-200 Pszczyna, ul. Piastowska 9
tel/fax (32) 2102211, 3263300, 2128822
e-mail sklep@unikomp.pl
internet www.wyswietlanie.pl