



## High Brightness Short-Throw Projector

### FEATURE

- Bright 3,300 ANSI lumens with a high 15,000:1 contrast ratio
- XGA resolution with a maximum resolution up to WUXGA
- Delivers a 77" diagonal image from less than 1 meter installation distance from the surface
- Short throw projection allows a presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- Assortment of connectivity options including HDMI 1.4b, VGA, S-Video, Composite Video, Audio-In/Out
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-ray support for dazzling and realistic life-like images
- 6 Segments (RYGCWB) colorwheel for accurate and detailed images
- Sealed optical engine to keep dust out and improve performance
- Integrated 10W audio speakers
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad

**UniKomp.pl**  
Nowe Technologie IT

adres	43-200 Pszczyna, ul. Piastowska 9
tel/fax	(32) 2102211, 3263300, 2128822
e-mail	sklep@unikomp.pl
internet	www.wyswietlanie.pl



The DX881ST is designed to cater for the education needs. The DX881ST delivers a 77" diagonal image from less than 1 meter installation distance from the surface. With a brightness of 3,300 ANSI Lumens and contrast ratio of 15,000:1 it delivers a perfect image display. The projector is designed for use in any classroom, small office or at home. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.

# DX881ST

## EDUCATION



## SPECIFICATIONS



<b>Display Type</b>	Single 0.55" DLP Technology by TI
<b>Brightness</b>	3,300 ANSI Lumens
<b>Native Resolution</b>	XGA (1024 x 768)
<b>Maximum Resolution</b>	WUXGA (1920x1200)@60Hz
<b>Contrast Ratio</b>	15,000:1
<b>Lamp Life and Type</b>	3500h/5000h/7000h, UHP Osram 240W/190W (Normal/Eco/Dyn. Eco)
<b>Throw Ratio</b>	0.62
<b>Image Size (Diagonal)</b>	60" ~ 200"
<b>Projection Distance</b>	0.76 ~ 2.52
<b>Projection Lens</b>	F2.8, f7.26mm
<b>Zoom Ratio</b>	Fixed
<b>Aspect Ratio</b>	4:3 Native
<b>Offset (full image height)</b>	114% (full image height)
<b>Keystone Correction</b>	+/-40 Degree; +/- 40 Steps
<b>Horizontal Frequency</b>	15, 31 - 91Hz
<b>Vertical Scan Rate</b>	24 - 30Hz, 47 - 120Hz
<b>Lens Shift Range</b>	n/a
<b>3D Compatibility</b>	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
<b>Audio</b>	10W (Mono)
<b>Video Compatibility</b>	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
<b>I/O Connection Ports</b>	HDMI v1.4b, VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack)(x3), VGA-Out, USB (Type A for 5V/1.5A Power Only), Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service), Microphone (Mini-Jack), 12V Trigger
<b>Security Solutions</b>	Kensington® Security Slot, Security Bar, Keypad Lock
<b>Dimensions (WxDxH)</b>	314 x 216 x 126 mm
<b>Weight</b>	3.2kg
<b>Noise Level</b>	36dB/32dB (Normal/Eco. Mode)
<b>Power</b>	Supply: AC 100-240V, 50/60Hz Consumption: 310W (Normal Mode), <0.5W (Standby Mode)
<b>Standard Warranty</b>	3 years projector / 1 year on lamp or 1000 hours whichever comes first
<b>Education Warranty</b>	5 years projector / 3 years on lamp or 2000 hours whichever comes first
<b>Standard Accessories</b>	AC Power Cord, VGA Cable, Remote Control, Lens Cap, Documentation Kit
<b>Optional Accessories</b>	Replacement Lamp: 5811119560-SVV
<b>UPC</b>	814964 339836

© Copyright 2014 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.

DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands